



SABA ENGINEERING WORKS

In The World of Plastics Processing Machinery.



3 Plate Side Toggle 5 Point Twin Locking Electrical

Vertical Scerw Type Plastic Moulding Machine. (5 Point Twin Side Toggle Locking In 3 Plate)

INJECTION UNIT

Screw Diameter	30/32 mm
Shot Capacity(PS)	60/80 gram
Maximum Pressure	1500 Kg/cm
Injection Stroke	10 to 150 mm
Hopper Capacity	10 kg

CLAMPING UNIT

Maximum Mould Size	265 x 330 mm
Maximum Mould Opening	200 mm
Distance Between Tiber	185 x 285 mm
Min/Max Mould Height	80 x 305 mm
Mould Locking Force	60 ton
Tiber Thickness	57 mm
Mould Ejector Center	Manual & Hydraulic

HYDRAULIC EQUIPMENT

Enjector Force	1.5 ton
Enjector Stroke	80 mm
Oil Tank Capacity	110 Liters
Hydraulic Parts	Yuken & Sufon
Pressure Control Valves	Polyhydron
Machine attach Oil Cooler Size	30 inch

ELECTRICALS

Heating Zone	3+1 qn
Heating Load	1x 3/3kw
Nozzle	250 w/1/4 w
Electric Motor Load	5/3.7 & 7.5/5.5 hp/kw
Total Connecting Load	7.1 & 8.9 kw

GENERAL

Floor Area	28 inch
Height	92 inch
Lenth	72 inch
Weight(Appox)	1200 kg

Machines MFG Co. Office & Work Shop

Importer & Exporter : Gala No.6, Ramji Patel, Compound, Pathan Wadi, Rani Sati Marg, Malad (East), Mumbai - 400097, Maharashtra, (India).

Mobile : 09322819493 / 09867404493 • Email ID : sabaenggworks@yahoo.in • Website : www.sabaengineeringwork.in/works.in

Branch Office : Delhi, NCR & North India • Mobile : 09818080915 / 09555552932 • Branch Office : Hyderabad - 9967963003